



# DAMPLOCK

CONCRETE & MASONRY CRACK FILLER

**SEAL-KRETE® DAMPLOCK™ Concrete & Masonry Crack Filler** is formulated as a general purpose latex caulk sealant and crack filler. Suitable for interior and exterior use, it can be used on concrete, brick, plaster, masonry, wood, metal, drywall, glass and tile. The gray color blends beautifully with concrete and stone, helping to improve the appearance of damaged and aging surfaces. In addition, DampLock Concrete & Masonry Crack Filler offers excellent adhesion and can be painted within 4-6 hours.

**APPLICATION**

**PREPARE:** The area to be repaired should be clean and dry. Use a wire brush to remove any loose material. Fill cracks deeper than 1/4" with backing material before applying sealant.

**APPLY:** Read "Limitations" and "Warnings" before use. Trim tip to desired bead size (45° angle) and load into standard caulk gun. Push sealant into crack, smoothing wet caulk with putty knife or sponge. Wait until dry before painting (about 4-6 hours, depending on temperature and humidity).

**LIMITATIONS:** Use only when air and surface temperatures are above 40°F and on cracks less than 1/2" wide. Do not use if rain or frost is expected within 24 hours of application. Not for use in marine applications or on surfaces submerged in water. Use within 1 year of manufacture.

**CLEAN-UP & STORAGE:** Clean tools immediately after use with soap and water. Do not store in extreme heat or cold; keep from freezing.

**WARNING: KEEP OUT OF REACH OF CHILDREN.** Do not take internally. Do not store or apply at temperatures below 40°F.

**WARRANTY:** Manufacturer/seller makes no warranty of any kind except that this product is free from defect and is of merchantable quality. Buyer remedy for breach of warranty is limited to replacement of product or refund of purchase price.

**TECHNICAL SUPPORT:** For assistance call 1-800-323-7357 (M-F, 8am-5pm EST) or visit [www.seal-krete.com](http://www.seal-krete.com).

**WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log onto [www.epa.gov/lead](http://www.epa.gov/lead).



**GRAY COLOR BLENDS INTO CONCRETE!**



PRODUCT NO.	DESCRIPTION	UNIT SIZE	UPC CODE	CARTON QTY.	CARTON BAR CODE	CARTON SIZE (L x W x H)	CARTON CUBIC FT.	CARTON WT. (LBS)	CARTONS / PALLET
851010	CONCRETE & MASONRY CRACK FILLER	10.1 OZ.	0 15944 85110 6	12	9 00 15944 85110 9	6.3 x 8.3 x 12.3	.37	15	100 CASES



**EASY TO TROWEL • HELPS REDUCE RADON GAS PENETRATION • INTERIOR/EXTERIOR USE**

How to treat concrete™

Convenience Products • 306 Gandy Road, Auburndale, FL 33823  
 E-mail: [tech@seal-krete.com](mailto:tech@seal-krete.com) or call 1-800-323-7357 • Visit our web site at [www.seal-krete.com](http://www.seal-krete.com)