

MATERIAL SAFETY DATA SHEET

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Seal-Krete® Damplock™ Crack Filler
PART NUMBER:
GENERAL USE: Latex caulk sealant
PRODUCT DESCRIPTION: Milky - white paste, characteristic mild odor



MANUFACTURER'S NAME Seal-Krete		DATE PREPARED: March 31, 2007	Page 1 of 4
		SUPERSEDES: New	
ADDRESS (NUMBER, STREET, P.O. BOX) 306 Gandy Road		TELEPHONE NUMBER FOR INFORMATION (800) 323-7357	
(CITY, STATE AND ZIP CODE) Auburndale, FL 33823-2723	COUNTRY USA	EMERGENCY TELEPHONE NUMBER Chemtrec (800) 424-9300 Outside USA (703) 527-3887	
DISTRIBUTOR'S NAME Same			
ADDRESS (NUMBER, STREET, P.O. BOX)		TELEPHONE NUMBER FOR INFORMATION	
(CITY, STATE AND ZIP CODE)	COUNTRY	EMERGENCY TELEPHONE NUMBER	

SECTION 2 - HAZARDOUS INGREDIENTS

HAZARDOUS COMPONENTS	% (by weight)	CAS #	EINECS #	Hazard Symbol	RISK PHRASES Full Text Section 16
Stoddard solvent (Petroleum distillate)	1 - 5	8052-41-3	232-489-3	Xn	R-10, 65
Ethylene glycol (a,b,c)	0.1 - 1.0	107-21-1	203-473-3	Xn	R-22
Diisooheptyl phthalate	Not specified	71888-89-6	276-158-1	NC	Not classified
Silica, crystalline, quartz (d,e)	0.1 - 0.8	14808-60-7	238-878-4	Xn	R-20, 36/37, 40

(a,c) See Section 15

(b) Indicates that the Resource Conservation and Recovery Act (RCRA) has determined the waste for this chemical is listed as hazardous and must be handled according to regulations in 40 CFR 260-281.

(d) Indicates substance appears on National Toxicology Program (NTP) list of carcinogens, International Agency for Research on Cancer (IARC) list of carcinogens or is regulated by the Occupational Safety and Health Administration (OSHA) as a possible carcinogen.

(e) California Prop 65, Safe Drinking Water and Toxic Enforcement Act of 1986, chemicals known to the state to cause cancer or reproductive toxicity. A person in the course of doing business must warn others who may consume, come into contact with, or otherwise be exposed to this chemical.

SECTION 3 - HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Mild paste, prolonged contact may cause eye irritation. Ingestion may cause gastric distress. Contains petroleum distillates, if ingestion occurs, do not induce vomiting. Contains crystalline quartz silica which is a hazardous respirable chemical. However, the silica is encapsulated in the product to the extent that airborne dust is not expected. Hazard Symbols for this product - None. Risk Phrase - Not classified

POTENTIAL HEALTH EFFECTS

INHALATION: None expected, however, certain individuals may experience minor nausea or headaches. Breathing airborne particles or dust from mixing, spraying, sanding, grinding, etc. may cause irritation to respiratory tract.

SKIN: None expected, however, prolonged contact may cause irritation.

EYES: Contact with eyes may cause irritation.

INGESTION: May result in vomiting; aspiration of vomitus into the lungs must be avoided; DO NOT induce vomiting. Minute amounts aspirated into the lungs can produce severe lung injury, chemical pneumonitis, pulmonary edema or death.

CARCINOGENICITY	NTP?	No	IARC MONOGRAPHS?	No	OSHA REGULATED?	No
-----------------	------	----	------------------	----	-----------------	----

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: Seal-Krete® Damplock™ Crack Filler
 March 31, 2007

Page 2 of 4

SECTION 4 - FIRST AID MEASURES

INHALATION: Remove affected person to fresh air; if symptoms persist seek medical attention.

SKIN: Remove contaminated clothing; wash affected area with soap and water; launder contaminated clothing before reuse; if irritation persists, seek medical attention.

EYES: Check for and remove contact lenses. Flush eyes with clear running water for 15 minutes while holding eyelids open; if irritation persists, seek medical attention.

INGESTION: DO NOT induce vomiting; if vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into lungs; seek immediate medical attention. Vomiting may be induced only under the supervision of a physician.

SECTION 5 - FIRE FIGHTING MEASURES

GENERAL HAZARDS: Product is not considered flammable or combustible. Products of combustion include compounds of carbon, hydrogen and oxygen, including carbon monoxide.

EXTINGUISHING MEDIA
 Carbon dioxide, water, water fog, dry chemical, chemical foam.

FIRE FIGHTING PROCEDURES
 Keep containers cool with water spray to prevent container rupture due to steam buildup; floor will become slippery if material is released.

UNUSUAL FIRE AND EXPLOSION HAZARDS
 None

HAZARDOUS COMBUSTION PRODUCTS
 Smoke, fumes or vapors, oxides of carbon.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Small spills - wash to sanitary sewer with plenty of water. Large spills - soak up with approved absorbent, shovel product into approved container for disposal. Wash area with plenty of water.

SECTION 7 - HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Keep container closed when not in use; protect containers from abuse; protect from extreme temperatures.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

HAZARDOUS COMPONENTS	NIOSH				ACGIH			
	TWA ppm	TWA mg/m3	STEL ppm	STEL mg/m3	TWA ppm	TWA mg/m3	STEL ppm	STEL mg/m3
Stoddard solvent (Petroleum distillate)	--	350	--	1800	100	572	--	--
Ethylene glycol (a,b,c)	--	--	--	--	39.4 C	127 C	39.4 (C)	127 (C)
Diisoheptyl phthalate	Not established				Not established			
Silica, crystalline, quartz (d,e)	--	0.05	--	--	--	0.05	--	--

(e) A "C" in the NIOSH or ACGIH columns indicates ceiling limits, the concentration that should not be exceeded during any part of the working exposure.

PERSONAL PROTECTION:
RESPIRATORY PROTECTION: NIOSH approved respirator designed to remove airborne particulate present in excess of maximum allowable concentrations due to secondary operations such as mixing, spraying, sanding, buffing, etc. Refer to 29 CFR 1910.134 or European Standard EN 149 for regulations.

PROTECTIVE GLOVES: Recommended for general protection

EYE PROTECTION: Safety glasses recommended for general protection Refer to 29 CFR 1910.133 or European Standard EN166.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Safety eyewash station nearby.

WORK / HYGIENIC PRACTICES: Practice safe workplace habits. Minimize body contact with this, as well as all chemicals in general.

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: Seal-Krete® Damplock™ Crack Filler
March 31, 2007

Page 3 of 4

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR Milky - white paste, characteristic mild odor	VAPOR PRESSURE 17 mm Hg @ 20° C
pH 7.5 - 8.0	SPECIFIC GRAVITY (WATER = 1) 1.187
BOILING POINT / BOILING RANGE 212° F (100° C)	SOLUBILITY IN WATER Emulsifiable
FLASH POINT Non-flammable	VISCOSITY Paste
FLAMMABLE LIMITS LEL: Not applicable UEL: Not applicable	VAPOR DENSITY (AIR = 1) > 1
AUTOIGNITION TEMPERATURE Not determined	EVAPORATION RATE (WATER = 1) < 1
VOLATILE ORGANIC COMPOUNDS (VOC's) Not determined	

SECTION 10 - STABILITY AND REACTIVITY

STABILITY UNSTABLE: STABLE: X	CONDITIONS TO AVOID: Extreme temperatures, keep from freezing.
INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizers, strong acids.	
HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Decomposition will not occur if handled and stored properly. In case of a fire, oxides of carbon, hydrocarbons, fumes or vapors, and smoke may be produced.	
HAZARDOUS POLYMERIZATION MAY OCCUR: WILL NOT OCCUR: X	CONDITIONS TO AVOID: None

SECTION 11 - TOXICOLOGICAL INFORMATION

Hazardous Components	CAS # EINECS #	LD50 of Ingredient (Specify Species and Route)	LC50 of Ingredient (Specify Species)
Stoddard solvent (Petroleum distillate)	8052-41-3	> 5000 mg / kg	> 5500 mg / m3 / 4H
	232-489-3	Oral - rat	Inhalation - rat
Ethylene glycol (a,b,c)	107-21-1	4700 mg / kg	10876 mg / kg
	203-473-3	Oral - rat	Inhalation - rat
Diisooheptyl phthalate	71888-89-6	Not established	Not established
	276-158-1		
Silica, crystalline, quartz (d,e)	14808-60-7	Not established	Not established
	238-878-4		

SECTION 12 - ECOLOGICAL INFORMATION

No data are available on the adverse effects of this material on the environment. Neither COD nor BOD data are available. Based on the chemical composition of this product it is assumed that the mixture can be treated in an acclimatized biological waste treatment plant system in limited quantities. However, such treatment should be evaluated and approved for each specific biological system. None of the ingredients in this mixture are classified as a Marine Pollutant.

SECTION 13 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: Dispose of in accordance with Local, State, and Federal Regulations. Product is classified as non - hazardous, however, non-hazardous materials may become hazardous waste upon contact with other products. Refer to "40 CFR Protection of Environment Parts 260 - 299" for complete waste disposal regulations. Consult your local, state, or Federal Environmental Protection Agency before disposing of any chemicals. According to the European Waste Catalogue, waste codes are application specific and should be assigned by the user based on the application for which the product is used.

SECTION 14 - TRANSPORT INFORMATION

PROPER SHIPPING NAME: Non - Hazardous for Transport	IATA HAZARD CLASS / Packaging Group: Not regulated
DOT HAZARD CLASS / Packaging Group: Not regulated	IMDG HAZARD CLASS: Not regulated
REFERENCE: Not Applicable	RID / ADR Dangerous Goods Code: Not regulated
UN / NA IDENTIFICATION NUMBER: None	UN TDG Class / Packaging Group: Not regulated
LABEL: None Required	Hazard Identification Number (HIN): None
HAZARD SYMBOLS: None	

Note: Transportation information provided is for reference only. Client is urged to consult CFR 49 parts 100 - 177, IMDG, IATA, EU, United Nations TDG, and WHMIS (Canada) TDG information manuals for detailed regulations and exceptions covering specific container sizes, packaging materials and methods of shipping.